

CORRECTED VERSION

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
24 June 2004 (24.06.2004)

PCT

(10) International Publication Number
WO 2004/052661 A1

(51) International Patent Classification⁷: B60B 3/14, F41H 11/16

(21) International Application Number: PCT/GB2003/005088

(22) International Filing Date: 21 November 2003 (21.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 0228899.1 11 December 2002 (11.12.2002) GB

(71) Applicant and

(72) Inventor: REECE, Alan, Richard [GB/GB]; Woodside, The Crescent, Wylam, Northumberland NE41 8HU (GB).

(74) Agent: VINSOME, Rex, Martin; Urquhart-Dykes & Lord LLP, St Nicholas Chamber, Amen Corner, Newcastle upon Tyne, NE1 1PE (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:


— with international search report

(48) Date of publication of this corrected version:

5 August 2004

[Continued on next page]

(54) Title: WHEEL ASSEMBLY FOR VEHICLE



(57) Abstract: A wheel assembly for a vehicle such as a tractor is disclosed. The assembly comprises a wheel rim (10) for supporting a tyre, a nave plate (11) mounted to the rim, and a drive plate (21) mounted to an axle flange (26). A torque ring (18) has first key ways (16, 17) for cooperating with first keys (14, 15) on nave plate (11), and second key ways (19, 20) for cooperating with second keys (22, 23) on drive plate (21). In this way, torque and radial and axial forces are transferred between the drive plate (21) and nave plate (11), but radial or axial forces, tending to remove the assembly from the axle, and exceeding respective predetermined levels, are prevented from being transferred from the nave plate (11) to the axle.



(15) Information about Correction:

see PCT Gazette No. 32/2004 of 5 August 2004, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.